

PARTNER

CARE . TRUST . RESPONSIBILITY

LABEL PRINTER LP-8300

80MM HYBRID THERMAL PRINTER



SPECIAL FEATURES

- Receipt and Label mode
- Supports wireless printing via Bluetooth or Wi-Fi
- Support scale connection and printing with clock module to show date and time on labels
- With cutter
- cashdrawer out
- Black mark and gap sensor

LP-8300

MODELL	LP-8300	
Print Method	Direct Thermal Printing	
Interface	Serial+USB standard; Wi-Fi option Bluetooth option	
Print Speed	127mm per second (label) 160mm per second (receipt)	
Print Width	80mm	
Print Length	120mm	
Emulation	TSPL (Label mode) ESC/POS (Receipt mode)	
Resolution	203dpi	
Paper Width	20~80mm	
Memory	Flash:128K (Label mode) Flash: 60K (Receipt mode)	
Media Diameter	3.1"	
Cutter y/n	Auto cutter, partial cut	
Barcode type	CODE128,EAN128,ITF,CODE39,CODE93,EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, UPCA, UPCA+2, UPCA+5, UPC-E, UPC-E+2,UPC-E+5, QRCode	
Printer weight	1.4kg	
Dimension	192x145x147mm (LxWxH)	
PS	external power adapter	
Condition	Operation Condition Temperature: 5-45°C Humidity: <93%RH	Storage Condition Temperature: -10-50°C Humidity: 10-90%RH
Image	Single color PCX and BMP files can be downloaded into Flash	
Paper type	Continuous thermal paper , thermal paper with interspaces , black mark paper	
Paper rolling up method	Printing side outward rolling	
The thickness of the paper	Max.0.254 mm(10 mil) Min.0.06 mm(2.36 mil)	
Gap size	Min.2 mm(0.09")	
Driver	Windows 2000 XP Vista Windows 7/8/8.1/10 Windows Server 2003&2008	
Software	Nicelabel, Labelshop	
Agency Approvals	CE, FCC, ROHS	

